UL Product iQ™



ZPMV2.E200612 - WIRING, PRINTED - COMPONENT

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

FAST PCB S L E200612

C/Gabiria 72 20305 Irun, SPAIN

Cond Width					Max			Max			
		Min	Cond	SS/	Area	Solder		Oper		Meets	C
	Min	Edge	Thk	DS/	Diam	Limits		Temp	Flame	UL796	T
Туре	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	С	sec	С	Class	DSR	ı
Multilayer printed wiring boards.											
FML1	0.127 (0.005)	0.127 (0.005)	17 (0.67) Int:70	DS	50.8 (2.0)	288	10	110	V-0	All	3
FML2	0.127 (0.005)	0.127 (0.005)	17 (0.67) Int:70	DS	50.8 (2.0)	288	10	130	V-0	All	3
Single layer printed wiring boards.											
ALF	0.127 (0.005)	0.127 (0.005)	16.5 (0.65)	DS	50.8 (2.0)	275	10	120	V-0	All	*
FAST	0.13 (0.005)	0.38 (0.015)	16.5 (0.65)	DS	12.7 (0.5)	260	10	130	V-0	All	3

^{* -} CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or trademark identification or burning test classification.

or file number and type designation. May be followed by a suffix to denote factory

Last Updated on 2019-07-10

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"